


## N-channel Enhanced mode TOLL MOSFET


### Features

- High ruggedness
- Low  $R_{DS(ON)}$  (Typ 1.1m $\Omega$ )@ $V_{GS}=4.5V$   
(Typ 0.8m $\Omega$ )@ $V_{GS}=10V$
- Low Gate Charge (Typ 118nC)
- Improved dv/dt Capability
- 100% Avalanche Tested
- Application: Synchronous Rectification, Li Battery Protect Board, Motor Drives



1. Gate 9.Drain 2~8.Source

$BV_{DSS}$  : 40V  
 $I_D$  : 360A  
 $R_{DS(ON)}$  : 1.1m $\Omega$ @ $V_{GS}=4.5V$   
 0.8m $\Omega$ @ $V_{GS}=10V$



### General Description

This power MOSFET is produced with advanced technology of SAMWIN. This technology enable the power MOSFET to have better characteristics, including fast switching time, low on resistance, low gate charge and especially excellent avalanche characteristics.

### Order Codes

Item	Sales Type	Marking	Package	Packaging
1	SW HE 010R04VLS	SW010R04VLS	TOLL	REEL

### Absolute maximum ratings

Symbol	Parameter	Value	Unit
$V_{DSS}$	Drain to source voltage	40	V
$I_D$	Continuous drain current (@ $T_C=25^\circ C$ )	360*	A
	Continuous drain current (@ $T_C=100^\circ C$ )	308*	A
$I_{DM}$	Drain current pulsed (note 1)	1440	A
$V_{GS}$	Gate to source voltage	$\pm 20$	V
$E_{AS}$	Single pulsed avalanche energy (note 2)	729	mJ
$E_{AR}$	Repetitive avalanche energy (note 1)	70	mJ
dv/dt	Peak diode recovery dv/dt (note 3)	5	V/ns
$P_D$	Total power dissipation (@ $T_C=25^\circ C$ )	312.5	W
	Derating factor above 25 $^\circ C$	2.5	W/ $^\circ C$
$T_{STG}, T_J$	Operating junction temperature & storage temperature	-55 ~ + 150	$^\circ C$

\*. Drain current is limited by junction temperature.

### Thermal characteristics

Symbol	Parameter	Value	Unit
$R_{thjc}$	Thermal resistance, Junction to case	0.4	$^\circ C/W$
$R_{thja}$	Thermal resistance, Junction to ambient	33	$^\circ C/W$

## Electrical characteristic ( $T_J = 25^\circ\text{C}$ unless otherwise specified )

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
<b>Off characteristics</b>						
$BV_{DSS}$	Drain to source breakdown voltage	$V_{GS}=0V, I_D=250\mu A$	40			V
$\Delta BV_{DSS} / \Delta T_J$	Breakdown voltage temperature coefficient	$I_D=250\mu A$ , referenced to $25^\circ\text{C}$		0.03		V/ $^\circ\text{C}$
$I_{DSS}$	Drain to source leakage current	$V_{DS}=40V, V_{GS}=0V$			1	$\mu A$
		$V_{DS}=32V, T_J=125^\circ\text{C}$			50	$\mu A$
$I_{GSS}$	Gate to source leakage current, forward	$V_{GS}=20V, V_{DS}=0V$			100	nA
	Gate to source leakage current, reverse	$V_{GS}=-20V, V_{DS}=0V$			-100	nA
<b>On characteristics</b>						
$V_{GS(TH)}$	Gate threshold voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	1		3	V
$R_{DS(ON)}$	Drain to source on state resistance	$V_{GS}=4.5V, I_D=30A, T_J=25^\circ\text{C}$		1.1	1.7	m $\Omega$
		$V_{GS}=10V, I_D=40A, T_J=25^\circ\text{C}$		0.8	1.3	m $\Omega$
		$V_{GS}=10V, I_D=40A, T_J=125^\circ\text{C}$		1.2		m $\Omega$
$G_{fs}$	Forward transconductance	$V_{DS}=5V, I_D=20A$		95		S
<b>Dynamic characteristics</b>						
$C_{iss}$	Input capacitance	$V_{GS}=0V, V_{DS}=20V, f=100\text{kHz}$		7945		pF
$C_{oss}$	Output capacitance			2428		
$C_{rss}$	Reverse transfer capacitance			81		
$t_{d(on)}$	Turn on delay time	$V_{DS}=20V, I_D=30A, R_G=4.7\Omega, V_{GS}=10V$ (note 4,5)		26		ns
$t_r$	Rising time			37		
$t_{d(off)}$	Turn off delay time			110		
$t_f$	Fall time			46		
$Q_g$	Total gate charge	$V_{DS}=32V, V_{GS}=10V, I_D=30A, I_G=5\text{mA}$ (note 4,5)		118		nC
$Q_{gs}$	Gate-source charge			22		
$Q_{gd}$	Gate-drain charge			19		
$R_g$	Gate resistance	$F=1\text{MHz}$		2.2		$\Omega$


## Source to drain diode ratings characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$I_S$	Continuous source current	Integral reverse p-n Junction diode in the MOSFET			360	A
$I_{SM}$	Pulsed source current				1440	A
$V_{SD}$	Diode forward voltage drop.	$I_S=50A, V_{GS}=0V$			1.4	V
$t_{rr}$	Reverse recovery time	$I_S=30A, V_{GS}=0V, di_f/dt=100A/\mu s$		71		ns
$Q_{rr}$	Reverse recovery charge				102	nC


### ※. Notes

1. Repeattive rating : pulse width limited by junction temperature.
2.  $L=0.5\text{mH}, I_{AS}=54A, V_{DD}=35V, R_G=25\Omega$ , Starting  $T_J=25^\circ\text{C}$
3.  $I_{SD} \leq 30A, di/dt = 100A/\mu s, V_{DD} \leq BV_{DSS}$ , Starting  $T_J=25^\circ\text{C}$
4. Pulse Test : Pulse Width  $\leq 300\mu s$ , duty cycle  $\leq 2\%$ .
5. Essentially independent of operating temperature.


**Fig. 1. On-state characteristics**




**Fig. 2. Transfer Characteristics**




**Fig. 3. On-resistance variation vs. drain current and gate voltage**



**Fig. 4. On-state current vs. diode forward voltage**



**Fig 5. Breakdown voltage variation vs. junction temperature**



**Fig. 6. On-resistance variation vs. junction temperature**




Fig. 7. Gate charge characteristics




Fig. 8. Capacitance Characteristics




Fig. 9. Maximum safe operating area




Fig. 10. Maximum drain current vs. case temperature




Fig. 11. Transient thermal response curve




Fig. 12. Gate charge test circuit & waveform




Fig. 13. Switching time test circuit & waveform




Fig. 14. Unclamped Inductive switching test circuit & waveform





Fig. 15. Peak diode recovery dv/dt test circuit & waveform



### DISCLAIMER

\* All the data & curve in this document was tested in SEMIPOWER TESTING & APPLICATION CENTER.

\* This product has passed the PCT,TC,HTRB,HTGB,HAST,PC and Solderdunk reliability testing.

\* Qualification standards can also be found on the Web site (<http://www.semipower.com.cn>) 

\* Suggestions for improvement are appreciated, Please send your suggestions to [samwin@samwinsemi.com](mailto:samwin@samwinsemi.com)