


N-channel Enhanced mode TO-247 MOSFET

Features

- High ruggedness
- Low $R_{DS(ON)}$ (Typ 65mΩ)@ $V_{GS}=10V$
- Low Gate Charge (Typ 74nC)
- Improved dv/dt Capability
- 100% Avalanche Tested
- Application: Charger, LED , UPS



1. Gate 2. Drain 3. Source

BV_{DSS} : 600V
I_D : 45A
R_{DS(ON)} : 65mΩ

A schematic symbol for an N-channel MOSFET. It consists of a circle with a vertical line through the center. The line has three terminals: one at the top labeled 1, one at the bottom labeled 3, and one on the right labeled 2. The symbol is enclosed in a rectangular box.

General Description

This power MOSFET is produced with super junction advanced technology of SAMWIN. This technology enable the power MOSFET to have better characteristics, including fast switching time, low on resistance, low gate charge and especially excellent avalanche characteristics.



Order Codes

Item	Sales Type	Marking	Package	Packaging
1	SW T 45N60K2F	SW45N60K2F	TO-247	TUBE

Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DSS}	Drain to source voltage	600	V
I_D	Continuous drain current (@ $T_C=25^{\circ}C$)	45*	A
	Continuous drain current (@ $T_C=100^{\circ}C$)	28*	A
I_{DM}	Drain current pulsed (note 1)	135	A
V_{GS}	Gate to source voltage	± 30	V
E_{AS}	Single pulsed avalanche energy (note 2)	854	mJ
E_{AR}	Repetitive avalanche energy (note 1)	85	mJ
dv/dt	MOSFET dv/dt ruggedness (@ $V_{DS}=0\sim 400V$)	30	V/ns
dv/dt	Peak diode recovery dv/dt (note 3)	20	V/ns
P_D	Total power dissipation (@ $T_C=25^{\circ}C$)	338	W
	Derating factor above 25°C	2.7	W/°C
T_{STG}, T_J	Operating junction temperature & storage temperature	-55 ~ + 150	°C
T_L	Maximum lead temperature for soldering purpose, 1/8 from case for 5 seconds.	300	°C

*. Drain current is limited by junction temperature.

Thermal characteristics

Symbol	Parameter	Value	Unit
R_{thjc}	Thermal resistance, Junction to case	0.37	°C/W
R_{thja}	Thermal resistance, Junction to ambient	35	°C/W

Electrical characteristic ($T_C = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
Off characteristics						
BV_{DSS}	Drain to source breakdown voltage	$V_{GS}=0V, I_D=250\mu A$	600			V
$\Delta BV_{DSS} / \Delta T_J$	Breakdown voltage temperature coefficient	$I_D=250\mu A$, referenced to 25°C		0.55		$V/^\circ\text{C}$
I_{DSS}	Drain to source leakage current	$V_{DS}=600V, V_{GS}=0V$			10	μA
		$V_{DS}=480V, T_C=125^\circ\text{C}$		120		μA
I_{GSS}	Gate to source leakage current, forward	$V_{GS}=30V, V_{DS}=0V$			100	nA
	Gate to source leakage current, reverse	$V_{GS}=-30V, V_{DS}=0V$			-100	nA
On characteristics						
$V_{GS(TH)}$	Gate threshold voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2.5		4.5	V
$R_{DS(ON)}$	Drain to source on state resistance	$V_{GS}=10V, I_D=22A$		65	83	$m\Omega$
G_{fs}	Forward transconductance	$V_{DS}=30V, I_D=22.5A$		30		S
Dynamic characteristics						
C_{iss}	Input capacitance	$V_{GS}=0V, V_{DS}=200V, f=1\text{MHz}$		3494		pF
C_{oss}	Output capacitance			109		
C_{rss}	Reverse transfer capacitance			2.3		
$t_{d(on)}$	Turn on delay time	$V_{DS}=300V, I_D=45A, R_G=25\Omega, V_{GS}=10V$ (note 4,5)		49		ns
t_r	Rising time			104		
$t_{d(off)}$	Turn off delay time			133		
t_f	Fall time			74		
Q_g	Total gate charge	$V_{DS}=480V, V_{GS}=10V, I_D=45A, I_g=3mA$ (note 4,5)		74		nC
Q_{gs}	Gate-source charge			25		
Q_{gd}	Gate-drain charge			30		
R_g	Gate resistance	$V_{DS}=0V$, Scan F mode		0.9		Ω

Source to drain diode ratings characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_S	Continuous source current	Integral reverse p-n Junction diode in the MOSFET			45	A
I_{SM}	Pulsed source current				135	A
V_{SD}	Diode forward voltage drop.	$I_S=45A, V_{GS}=0V$			1.4	V
t_{rr}	Reverse recovery time	$I_S=20A, V_{GS}=0V, di/dt=100A/\mu s$		191		ns
Q_{rr}	Reverse recovery charge			1.46		μC

※. Notes

1. Repeattive rating : pulse width limited by junction temperature.
2. $L=26.7mH, I_{AS}=8A, V_{DD}=50V, R_G=25\Omega$, Starting $T_J=25^\circ\text{C}$
3. $I_{SD} \leq 20A, di/dt = 100A/\mu s, V_{DD} \leq BV_{DSS}$, Starting $T_J=25^\circ\text{C}$
4. Pulse Test : Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.
5. Essentially independent of operating temperature.

Fig. 1. On-state characteristics




Fig. 2. Transfer Characteristics




Fig. 3. On-resistance variation vs. drain current and gate voltage




Fig. 4. On-state current vs. diode forward voltage




Fig. 5. Breakdown voltage variation vs. junction temperature




Fig. 6. On-resistance variation vs. junction temperature




Fig. 7. Gate charge characteristics




Fig. 8. Capacitance Characteristics




Fig. 9. Maximum safe operating area




Fig. 10. Transient thermal response curve




Fig. 11. Gate charge test circuit & waveform




Fig. 12. Switching time test circuit & waveform




Fig. 13. Unclamped Inductive switching test circuit & waveform





Fig. 14. Peak diode recovery dv/dt test circuit & waveform



DISCLAIMER

- * All the data & curve in this document was tested in SEMIPOWER TESTING & APPLICATION CENTER.
- * This product has passed the PCT,TC,HTRB,HTGB,HAST,PC and Solderdunk reliability testing.
- * Qualification standards can also be found on the Web site (<http://www.semipower.com.cn>) 
- * Suggestions for improvement are appreciated, Please send your suggestions to samwin@samwinsemi.com